GENUINE APITONG

Shiplap | Rough | S4S



APITONG: DURABLE AND TRUSTED

Apitong, also known as Keruing, is renowed for its exceptional strength-to-weight ratio. Apitong has been the preffered hardwood for flatbed trailer decking and industrial applications for over 25 years. Its heartwood varies from brown to dark brown or light to dark red-brown, sometimes with a hint of purple, and is well-defined from the buff colored or gray sapwood. Apitong's uniform straight grain and moderately coarse texture contribute to its durablity and resilience uder heavy loads.

UNMATCHED STRENGTH AND LONGEVITY

Apitong hardwood is celebrated for its incredible strength, resilience, and longevity. Its dense grain structure and natural durability make it ideal for enduring the wear and tear of heavy equipment, shifting cargo, and challenging weather conditions. With a proven track record spanning decades, Apitong has consistently outperformed alternative hardwoods in both performance and cost-effectiveness, making it the go-to choice for trailer decking across the globe.





TECHNICAL SPECIFICATIONS

Janka Hardness: 1,520 lbf

Strength (MOR): 19,900 psi

Stiffness (MOE): 2,070,1000 p

Stiffness (MOE): 2,070 1000 psi

Density (kg/m³): 790

Color: The heartwood of Aptiong ranges from brown to dark brown, light to dark red-brown with hints of

purple. Sapwood is buff or gray colored.

Photosensitivity: Moderate

Species: Dipterocarpus grandiflorus

Tree Characteristics: The Angelim Pedra tree can reach up to 150 feet in height and 10 feet in diameter. Geographic Area: Apitong can be found across southeast Asia, primarily in countries like Malaysia, Indoneasia, Thailand, and the Philippines.

Texture: Moderately Course Grain: Straight to interlocked

Luster: Low to moderate

Durability Rating: Very durable and resistant to wear,

decay, and insect attacks.

Nova USA Wood Products 3821 24th Ave. Forest Grove, OR. 97116 (503) 419-6407



@NOVAUSAWOOD